

## **FEATURE**

- Injection-molded thermoplastic ABS housing, UL 94V-0 flame rating.
- Innovative, easy installation in minutes.
- Suitable for wall mount applications.
- Universal J-box mounting pattern.
- 120V-277VAC Dual voltage operation.
- 2X1W 2835 LED lamp heads for emergency mode.
- Luminous Flux:more than 200 LM.
- Built-in 3.6V1000mAh Nickel cadmium battery for minimum
- 90 minutes emergency operation.
- Maximum 24 hours for full recharge time.
- Test switch and charge indicator.
- UL and cULus listed.
- 0° to 40° C indoor damp location listed.
- Five years warranty for the electrical parts and housing.
- Three years warranty for battery.

ORDERING INFORMATION				
<u>FAMILY</u>	HOUSING COLOR			
JLEU10	BLANK(WHITE)			
	B(BLACK)			

PACKING INFORMATION					
MODEL NO .	PACKING INFORMATION	WEIGHTS			
JLEU10	40x27x15.5cm/6pcs	4.5/3.5kgs			

NOTES:


TYPE: ADJUSTABLE DUAL HEAD EMERGENCY LIGHT






CEC DOE F©







ELECTRICAL INFORMATION							
MODEL	RATED VOLTAGE	INPUT CURRENT	INPUT WATT	LED TYPE	CHARGING TIME	EMERGENCY RUN TIME	
JLEU10	120-277V	0.066A	2W	2×1W 2835 LED lamp heads	24 Hrs	90 Mins	