

FEATURE

- Injection-molded thermoplastic ABS housing and polycarbonatecover, UL 94V-0 flame rating.
- Innovative, easy installation in minutes
- Suitable for wall and ceiling mount applications
- Universal J-box mounting pattern
- 120V/277VAC Dual voltage operation
- 2X12pcs Super bright 2835 0.5W LED lamp heads for emergency mode, provide more than 400Lm output.
- Built-in 3.6V2000mAh Nickel cadmium battery for minimum90 minutes emergency operation.
- Maximum 24 hours for full recharge time
- Test switch and charge indicator
- UL and cULus Wet location listed
- 0° to 40°C indoor damp location listed
- Five years warranty for the electrical parts and housing.
- Two years warranty for battery.

ORDERING INFORMAION									
FAMILY	HOUSING COLC	DR	WET LOCATION						
JLEU5WP	BLANK(WHITE)	B(BLACK)	G(GREY)	WP(WATER PROOF)					


PACKING INFORMATION						
MODEL NO .	PACKING INFORMATION	WEIGHTS				
JLEU5WP	45.2x34x27.5cm/6pcs	7/6kgs				



FAMILY : LXA-JLEU5WP







MODEL	RATED VOLTAGE	INPUT CURRENT	INPUT WATT	LED TYPE	CHARGING TIME	EMERGENCY RUN TIME			
JLEU5WP	120/277V	0.025/0.010A	2.4W	2×12pcs ultra bright 2835 SMT LED lamp	24 Hrs	90 Mins			